



GRABO IDEAL

Technical parameter	Standard	Unit	Result
DESCRIPTION			
Constraction			Luxury Vinyl Tile
Plank size	EN ISO 24341	mm	185 x 1220
	EN ISO 24341	mm	158 X 950
Tile size	EN ISO 24341	mm	305 x 610
Total thickness	EN ISO 24346	mm	2.7
Wear layer thickness	EN ISO 24340	mm	0.7
Total weight	EN ISO 23997	kg/m2	3.9
CLASSIFICATION			
Binder content	EN ISO 10582		Type I.
European classification	EN ISO 10582	class	23 / 34 / 43
Residual indentation	EN ISO 24343-1	max. mm	0.1
Dimensional stability	EN ISO 23999	max. %	0.15
Curling	EN ISO 23999	max. mm	2
PERFORMANCE			
Abrasion group	MSZ EN 660-2	class	T
Fire resistance	EN 13501-1	class	Bfl-s1
Slip resistance	EN 13893		DS
	DIN 51130	class	R10
Electrical propensity	EN 1815	max. kV	2 / Antistatic
Light fastness	EN ISO 105-B02	grade	6
Chemical resistance	EN ISO 26987		✓
Hygenie			Bacterial resistant
Castor chair resistance	EN 425 / ISO 4918		✓
Surface treatment			iGUARD PUR Surface
Environmental attributes			Solvent and Phthalate free
Content of PCP	EN 12673		does not contain
Formaldehyde emission	ENV 717-1		E1 (no emission)
VOC			Pass